



CHARACTERISTICS

- MOTORIZED BELTS FOR MODULE TRANSPORTATION
- SAFE MODULE GRIP WITH 6 VACUUM SUCTION CUPS
- INTEGRATED PNEUMATIC LIFTER WITH 360° ROTATION
- EASY INTEGRATION IN ANY PRE-EXISTING LINE
- INLINE OR STAND ALONE UNIT
- ROBUST AND FUNCTIONAL DESIGN

**MULTI
WORK
TABLE**

**SUITABLE FOR
BACK CONTACT
POLY/MONO
PERC, HIT
BIFACIAL**

**SAFETY
KNIFE
INCLUDED**

OPTIONAL:

**FULLY AUTOMATIC SOLUTION
ECOTRIM A**

PRODUCTION OPERATIONS:

- MANUAL TRIMMING
- EDGE TAPING FOR GLASS+GLASS
- BUTYL EDGE SEALING FOR GLASS+GLASS
- CENTRAL MANUAL BUSSING, FOUR HALF CUT
- AUTOMATIC CONVEYOR FOR J-BOX POSITIONING
- CLEANING STATION



TECHNICAL SPECIFICATIONS

| | |
|---------------------|--|
| LOADING & UNLOADING | Motorized loading and unloading belts |
| MODULE ORIENTATION | Long edge forward |
| CONFIGURATION | Inline or Stand alone |
| CONTROL | Pedal for lifting system, Manual handling for turning 360° |
| REMOTE ASSISTANCE | Internet |

UTILITY SPECIFICATIONS

| ELECTRICAL CHARACTERISTICS | |
|----------------------------|------------|
| LINE | 3P+N+E * |
| VOLTAGE | 400 V * |
| FREQUENCY | 50/60 Hz * |
| PEAK POWER | 5 kW |
| POWER CONSUMPTION | 4 kW |
| MAX CURRENT | 9 A |
| PRE FUSE | 10 A |
| AIR CHARACTERISTICS | |
| AIR PRESSURE | 6 bar |
| AIR CONSUMPTION | 3 NL/1' |
| AIR PEAK FLOW | 5 NL/1' |
| AIR CONNECTION | 1/4" |
| DIMENSIONS | |
| HEIGHT | 1000 mm |
| LENGHT | 2300 mm |
| WIDTH | 1400 mm |
| CE WEIGHT | 200 kg |