



### CHARACTERISTICS

- ROTATES TO FACE THE OPERATOR
- SEMI-AUTOMATIC ROTATION CONTROLLED BY PEDAL OR MANUAL ROTATION
- STRONG VACUUM SYSTEM WITH 6 SUCTION CUPS PREVENTS MODULES FROM DROPPING OUT
- STATION FOR VISUAL INSPECTION AND CLEANING
- CAN BE PROVIDED WITH LED BACK LIGHTING
- CAN BE PROVIDED WITH A TURNING UNIT
- PROVIDED WITH PROTECTION BARRIERS

**SUITABLE  
ALSO FOR  
GLASS+GLASS**

### OPTIONALS

**CUSTOMIZABLE AREA**

**LED BACK LIGHTING**

**CONVEYOR WITH HORIZONTAL TURNING UNIT**

Images for illustrative purposes only

ECOPROGETTI Srl - Italy

Via dell'Industria e dell'Artigianato, 22/D, Carmignano di Brenta, 35010 - Padua

Tel. +39 049 7444900 - info@ecoprogetti.com - www.ecoprogetti.com



## UTILITY SPECIFICATIONS

ELECTRICAL CHARACTERISTICS	
LINE	3P+N+E
VOLTAGE	400 V
FREQUENCY	50/60 Hz
PEAK POWER	1 kW
POWER CONSUMPTION	1 kW
MAX CURRENT	3 A
PRE FUSE	4 A
AIR CHARACTERISTICS	
AIR PRESSURE	6 bar
AIR CONSUMPTION	<1 NL/1'
AIR PEAK FLOW	<1 NL/1'
AIR CONNECTION	1/4"
DIMENSIONS	
HEIGHT	2500 mm
LENGHT	4000 mm
WIDTH	2900 mm
CE WEIGHT	1100 mm