



CHARACTERISTICS

- UP TO 15 MODULES STORAGE (OPTIONAL 50);
- PROVIDED OF PLC TOUCH SCREEN (CONFIGURABLE WITH LAMINATOR)
- PICK AND PLACE WITH AUTOMATIC DRAWER
- FIFO "FIRST IN, FIRST OUT" CONCEPT
- STORAGE MODE OR STRAIGHT-THROUGH FUNCTION
- MODULE FORMAT: max 2300x1400mm, min 450x450mm
- SUITABLE ALSO FOR GLASS GLASS MODULES

CAPACITY
15
MODULES

BEFORE
OR AFTER
LAMINATION

OPTIONALS

MORE LAYERS, MORE MODULES.

Max 50 Modules



TECHNICAL SPECIFICATIONS

MODULE SIZE	max 2300x1400mm, min 450x450 mm
MODULE ORIENTATION	Long-edge forward
MODULE LOADING/UNLOADING	Automatic
CONFIGURATION	Inline
APPLICATION	Before or After Lamination
CONTROLS	PLC Touch screen
MODULE STORAGE	Standard 15 modules ; Custom 50 modules
FUNCTION	Storage function or Straight-through
LIFTING	Automatic Drawer for pick and place

UTILITY SPECIFICATIONS

ELECTRICAL CHARACTERISTICS	
LINE	3P+N+E
VOLTAGE	400 V
FREQUENCY	50/60 Hz
PEAK POWER	2,5 kW
MEAN POWER	2 kW
MAX CURRENT	8 A
PRE FUSE	16 A
DIMENSIONS	
HEIGHT	2500 mm
LENGHT	2000 mm
WIDTH	3900 mm
WEIGHT	4200 kg

* Available also with different voltages, according to criteria of the place of installation. To be defined at order if with implementation of transformers or with modification of the electrical board of the machine.